

WILD BUNCH CLASS (Traditional)

PISTOL

1911 style semi auto in 45 ACP
Single stack magazine W/ 8rds Max.
5" barrel, No Porting or Compensators
Fixed sights only, Non Adjustable
G I style wood or plastic grips, No rubber or target style
Standard grip safety only, NO Beavertail
Standard slide release & safety, NO extended models
Standard Hammer (Spur)
Standard recoil spring & guide
Short or Long Trigger only (NO Target)
Only factory ejection ports
NO checkering on front strap or trigger guard

RIFLE

Any Main Match rifle in pistol caliber of .40 CAL or larger

SHOTGUN

1897 Winchester pump only, original or replica
Magazine may be loaded prior to shooting w/ hammer down on empty chamber

HOLSTERS & MAG POUCHES

Traditional or Military style of canvas or leather, must cover barrel from muzzle
to ejection port
NO Shoulder or cross draw
Magazine pouches must be worn opposite to pistol holster, Must be Vertical,
NO tip out pouches
Pouch MUST cover minimum of 2" of magazine

AMMUNITION

Only LEAD slugs allowed
Standard SASS Velocities in place
Pistol 1000 F P S
Rifle 1400 F P S

STAGE OPERATIONS (continued on next page)

STAGE OPERATIONS

Shooter will start stage at loading position, Magazines loaded w/ 5rds only
1 mag inserted in pistol, hammer down on Empty chamber
ON BEEP. Shooter will engage stage a any other shooter with the exception
that at end of 1st pistol string slide must be locked back, &
pistol staged SAFELY on prop. DO NOT REHOLSTER
After final pistol string Slide is locked back, R. O. MUST CHECK for empty
chamber, Magazine is Ejected, Slide is closed on empty pistol
& GUN is reholstered

Magazines may ONLY BE LOADED W/ 5rds each
Shooter may move with pistol in hand ONLY if slide is locked back with either
an empty magazine inserted, or NO magazine & finger OUTSIDE
trigger guard
Shooter may also move with pistol in hand with hammer down on empty chamber
& loaded magazine in pistol
Magazine may be changed on the move with slide locked back & finger
OUTSIDE trigger guard
Shooter has the choice of loading the 1897 winchester at the loading position
or loading on the clock, If loading at loading position, hammer
MUST BE DOWN ON AN EMPTY CHAMBER

UNLOADING POSITION

Standard unloading procedures will be followed with the exception that
the pistol is not checked again